

# KleenGIANT<sup>34SL series</sup>

## PARTS CLEANER WITH AUTOMATIC SOLVENT RECYCLING



34SL-37  
(37" WIDE SINK)



A closed loop system



34SL-42  
(42" WIDE SINK)

Variety of parts are cleaned in the rugged stainless steel sink using the Flow-Thru Brush and Flexible Spigot. The Built-in Solvent Recycler provides a supply of clean solvent.

**Delivers  
Clean Solvent  
in about  
Sixty Seconds!**

### Built-in Solvent Recycler

- Clean solvent is available on demand. With a press of the button, clean solvent is available in about 60 seconds.
- The unit produces up to 20 gallons of clean solvent per day (4 batches at 5 gallons per batch).
- The recycler unit may be started by the press of a button or on an automatic scheduled start.
- Waste Sludge is automatically discharged into a waste container.
- Dramatic saving in solvent purchases and disposal costs.



# KleenGIANT 34SL

## PARTS CLEANER WITH AUTOMATIC SOLVENT RECYCLING

### MODELS

Model No.	Sink Size (")	Shipping Dimensions(")	Shipping Weight (lb)
34SL-37	37W x 28D x 8H	40W x 48D x 50H	420
34SL-42	42W x 30D x 8H	40W x 48D x 50H	450
34SL-42S*	42W x 30D x 9.5H	40W x 48D x 50H	450

\* Stainless Steel Cabinet

### FEATURES

Wash Sink Solvent Tank	Five Gallons
Solvent Reserve Capacity	Fifteen Gallons of Clean Solvent
Sink & Tank Construction	100% Stainless Steel
Wash & Transfer Pumps	High Pressure Dual Diaphragm
Solvent Flow Controls	Timer and Hands-Free Foot Pedal
Cleaning Tools	Flow-Thru Brush & Flexible Spigot
Technology	Direct Heating technology, resulting in low maintenance and quiet operation; designed without diathermic oil to change and motor driven vacuum pump to maintain.
Residue Disposal	Drains automatically into pail, designed to contain any solvent odor.
Automatic Recycle Start	Programmable based on solvent usage.
Recycle Time	About Five Gallons in Five Hours
Clean Solvent Transfer	One Minute
Solvent Level Indicator	Visual Gage, LCD message and Audible Alarm
Clean Solvent Top-Off	Fast & Easy Thru Lid Opening in Clean Tank
Serviceability	Sophisticated Micro Processor w/ Self Diagnostics Full modular construction for ease of service and maintenance. Recycler unit is easily removed in one minute.
Utility Requirements	120 V, 1600 W (240 V models are available) Air Supply, 85 PSI minimum, 2 CFM
Safety Certifications	UL Standards U2208 and CSA Standard C22.2 NO.30 and NO.80 by ETL. Also certified for use in Hazardous Locations Class 1, Division 1 and 2, group D-T2C as well as all Non-Hazardous locations.



**CALL LOCAL DISTRIBUTOR FOR DEMONSTRATION**



**USA 800-477-9133**  
245 Cooper Ave., Suite 108  
Tonawanda, NY 14150  
Fax: 905-477-8922  
salesusa@uniram.com

[www.uniram.com](http://www.uniram.com)

**INTERNATIONAL**  
381 Bentley Street,  
Markham, Ontario,  
Canada L3R 9T2  
Tel: 905-477-5911  
Fax: 905-477-8922  
salescan@uniram.com

Over 10,000 Customers have used Uni-Ram Solvent Recyclers.