



THE MOBILE VACUUMS UR700QVAC AND UR400QVAC

KEEPS YOUR SHOP DUST FREE WHILE SANDING



Mobile Vacuum moves easily to work area due to handle, large wheels and low center of gravity.

UR400QVAC



UR700QVAC

BENEFITS

- Cleaner and healthier shop environment
- Technicians breathe freely, no need for breathing apparatus.
- Recently painted parts are dust free .
- Reduces clean up time.
- Reduces sand paper consumption.
- Complements or even eliminates need for central vacuuming system.

ASSISTS SHOP IN MEETING AIR QUALITY STANDARDS

CONTROL PANEL FOR UR700QVAC



TWO STAGE FILTER



- Both filters are easy to replace.

SANDER



UR700QVAC

- Two operators can work at same time - each hose is 16 ft, power cord is 20 ft.
- Features Shown on Control Panel For UR700QVAC
 - Automatic Switch: ON / OFF control at sander automatically turns vacuum on and off. Manual: Turns Vacuum on and off, manual override.
 - Motor: Select single or dual (2) vacuum motors, single = 1,000 W and dual = 2,000 W. Maximum decibel rating at 2,000 W is 70 db.
 - Variable Power: Power consumption and sound can be reduced at each motor setting when maximum power is not required.
 - Electrical Outlet
- Voltage: 120 V. 60 Hz. for UR700QVAC
240 V 50 / 60 Hz for UR700QVACH
- Stainless steel drum construction (12 Gal, 47 L) capacity.
- Can be used as a wet vac with optional kit - part number 28-7810.
- Vacuum Pressure: 99 inH₂O
- Dimensions 41" h x 31" w x 21" d
- Weight 66 lb / 30 kg

UR400QVAC

- For one operator - hose is 16 ft, power cord is 20 ft.
- Motor: 1 motor at 1,000 W. Maximum decibel rating is 70 db.
- Optional 2nd hose is available for 2nd operator. Note: the UR700QVAC is the VAC of choice for 2 operators because the power rating is 2,000 W vs 1,000 W for the UR400QVAC.
- Automatic Switch: ON / OFF control at sander automatically turns vacuum on and off. Manual: Turns Vacuum on and off, manual override.
- Voltage: 120 V, 60 Hz . for UR700QVAC
240 V, 50/ 60 hZ. for UR700QVACH
- Stainless steel drum construction.
- Vacuum Pressure: 45 inH₂O
- Dimensions 32" h x 18" w x 30" d
- Weight 55 lb / 25 kg

OPTIONAL PARTS

- Cartridge Filter, **High Density** 28-172
- Vacuum Hose and Brush Kit for Wet / Dry vacuuming (for UR700QVAC only) 28-710
- 24 ft. VAC and air hose 28-724

SANDERS

- UPSANDER 6" Pad, 5 mm offset, 1.7 lb, 90 PSI, 8.4 cfm
 - UPFSANDER 6" Pad, Fine, 2.5 mm offset, 1.7 lb, 90 PSI, 8.4 cfm
- Note: Sanders are sold separately. (not included with VACs)

SAFETY APPROVALS ON VACS

- UL, CE, CSA Safety Approval

1 Year Warranty